

Wall mounted unit

AC fan motor unit for wall mounting

- › High aesthetic cabinet design
- › Optimum air distribution
- › Easy to install
- › Wireless remote control up to 9 m distance
- › 3-speed fan motor
- › Wide operating range
- › Low operating sound level thanks to tangential fan
- › Insulated with self-extinguishing class 1 heat insulation
- › Removable washable air filter (self-extinguishing class 1)



Indoor unit				FWT-GT	02	03	04	05	06	
				2-pipe						
Cooling capacity (standard conditions)	Total capacity	High	kW	2.40	2.67	3.27	4.49	5.21		
	Sensible capacity	Medium	kW	2.20	2.23	2.79	4.02	4.32		
		Low	kW	1.94	2.02	2.52	3.76	4.04		
		High	kW	1.82	1.99	2.60	3.38	4.03		
Heating capacity (standard conditions)	Medium	High	kW	1.73	1.69	2.21	3.00	3.52		
		Medium	kW	1.50	1.49	1.91	2.77	3.22		
		Low	kW	2.71	2.96	3.71	5.07	6.23		
	Low	kW	2.41	2.62	3.29	4.51	5.38			
Power input	High	kW	2.06	2.25	2.75	4.03	4.83			
	Medium	kW	0.031	0.032	0.042	0.053	0.072			
	Low	kW	0.03		0.04	0.05	0.07			
FCEER				0.03		0.04	0.05	0.06		
FCCOP				D		C	C	D		
Dimensions	Unit	HeightxWidthxDepth	mm	288x800x206			310x1,070x224			
Weight	Unit			9.00			14.0			
Casing	Colour	White								
Air filter	Type	Washable Saranet								
Fan	Type	Cross flow fan								
Total sound power level	Quantity	1								
		Air flow rate	High	m ³ /h	442	476	629	866	1,053	
			Medium	m ³ /h	391	425	544	765	883	
			Low	m ³ /h	340	374	442	663	782	
Sound pressure level	High	dBA	45.0	48.0	55.0		59.0			
	Medium	dBA	41.0	44.0	50.0	51.0	54.0			
	Low	dBA	36.0	39.0	45.0	47.0	51.0			
Sound pressure level	High	dBA	34.0	35.0	42.0		46.0			
	Medium	dBA	29.0	30.0	39.0	38.0	42.0			
	Low	dBA	25.0		32.0	34.0	39.0			
Piping connections	Drain	OD	mm	19						
Power supply	Phase/Frequency/Voltage		Hz/V	1N~/50/220-240						
Control systems	Infrared remote control		WRC-HPC							
	Wired remote control		MERC-A / SRC-HPA							

For standard conditions refer to the Measuring Conditions table, at the end of this catalogue