

9. Τεχνικά χαρακτηριστικά

ITEM		MODEL	KDB-172FA	KDB-200FA	KDB-200FA(C)	KDB-250FA	KDB-250FA(C)	KDB-350FA	KDB-350FA(C)
HEAT OUTPUT		kcal/h	17,000	20,000	20,000	25,000	25,000	35,000	36,000
HOT WATER OUTPUT		kcal/h	17,000	20,000	20,000	25,000	25,000	35,000	36,000
FOR USE		—	HEATING & HOT WATER						
FUEL		—	KEROSENE, LIGHT-OIL						
ROOM SIZE		m ²	Less Than 112	Less Than 132	Less Than 132	Less Than 165	Less Than 165	Less Than 231	Less Than 231
TEMPERATURE OF EXHAUSTED GAS		℃	Less Than 250						
PEAK PRESSURE		kgf/cm ² (bar)	2.5		3.0	2.5	3.0	2.5	3.0
HEATING SIZE		m ²	0.79			0.98		1.21	0.98
FUEL CONSUMPTION		ℓ/h	2.27	3.15		3.55		4.77	5.00
TOTAL HEATING EFFICIENCY	FF	%	92.5						91.0
	FE	%	90.0						
RANGE OF TEMP			52 ~ 80						20 ~ 85
POWER CONSUMPTION		W	60	66	135	71	140	82	187
POWER		V, Hz	220.50						
WATER STORAGE CAP		ℓ	30			40		45	40
EXTERNAL SIZE		W×L×Hmm	362×632×855		470 ×706 ×900	362 ×632 ×855	510 ×760 ×910	402 ×632 ×855	510 ×760 ×905
WEIGHT		kg	65	67	88	74	104	83	104
PIPING	HEATING CONNECTION	A	25			32	25	32	25
	HOT WATER CONNECTION	A	15						
DIAMETER OF FUEL		mm	INHALE : 60, EXHAUST : 75						

* ΤΑ ΠΑΡΑΠΑΝΩ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ ΜΠΟΡΕΙ ΝΑ ΑΛΛΑΞΟΥΝ ΧΩΡΙΣ ΠΡΟΕΙΔΟΠΟΙΗΔΗ.

MODEL		ITEM		KDB-172ST	KDB-203ST	KDB-253ST	KDB-353ST	KDB-203STC	KDB-253STC	KDB-353STC
HEAT OUTPUT		kcal/h		17,000	20,000	25,000	35,000	20,000	25,000	35,000
HOT WATER OUTPUT		kcal/h		17,000	20,000	25,000	35,000	20,000	25,000	35,000
FOR USE		—	HEATING & HOT WATER							
FUEL		—	KEROSENE, LIGHT-OIL							
ROOM SIZE		m ²		Less Than 112	Less Than 132	Less Than 165	Less Than 231	Less Than 132	Less Than 165	Less Than 231
TEMPERATURE OF EXHAUSTED GAS		℃	Less Than 250							
PEAK PRESSURE		kgf/cm ² (bar)	3.5							
HEATING SIZE		m ²		0.84	0.92	1.08	1.43	0.92	1.08	1.43
FUEL CONSUMPTION		ℓ/h		2.27	2.54	3.55	4.54	2.54	3.55	4.54
TOTAL HEATING EFFICIENCY	FF	%		94.4	94.4	93.8	93.8	94.4	93.8	93.8
	FE	%		94.4	94.4	93.8	93.8	94.4	93.8	93.8
RANGE OF TEMP			52 ~ 80							
POWER CONSUMPTION		W		63	65	65	110	125	138	179
POWER		V, Hz	220.50							
WATER STORAGE CAP		ℓ		18	20	25	31.6	20	25	31.6
EXTERNAL SIZE		W×L×Hmm		322 × 520 × 800	322 × 520 × 860	350 × 550 × 855	402 × 691 × 910	430 × 611 × 860	470 × 706 × 900	510 × 760 × 910
WEIGHT		kg		42	44	48	68	66	86	98
PIPING	HEATING CONNECTION	A	25				32	25		
	HOT WATER CONNECTION	A	15							
DIAMETER OF FUEL		mm	INHALE : 60, EXHAUST : 75							

* ΤΑ ΠΑΡΑΠΑΝΩ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ ΜΠΟΡΕΙ ΝΑ ΑΛΛΑΞΟΥΝ ΧΩΡΙΣ ΠΡΟΕΙΔΟΠΟΙΗΔΗ.