

Alternative Code		GWH09AAXB-K6DNA2B		GWH12AAXB-K6DNA2A		GWH18AAD-K6DNA2E		GWH24AAD-K6DNA2B	
		Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Nominal performance	Btu/h (W)	8530 (2500)	9554 (2800)	10918 (3200)	11600 (3400)	15700 (4600)	17742 (5200)	21000 (6200)	22000 (6500)
Performance range	Btu/h (W)	1706 - 11089 (500 - 3250)	1706 - 12283 (500 - 3600)	3071 - 12283 (900 - 3600)	3071 - 13648 (900 - 4000)	3412 - 18084 (1000 - 5300)	2388 - 19278 (1000 - 5650)	6100 - 23500 (1800 - 6900)	4400 - 24000 (1300 - 7033)
Consumption (min-nom-max)	W	150 - 680 - 1300	140 - 730 - 1500	220 - 991 - 1300	220 - 916 - 1500	420 - 1355 - 1800	420 - 1340 - 1900	450 - 1827 - 2200	450 - 1912 - 2300
SEER/SCOP		6.6	4,1/5,1	6,1	4,0/5,1	6,4	4,0/5,1	6.8	4,0/5,1
Energy class		A++	A+/A+++	A++	A+/A+++	A++	A+/A+++	A++	A+/A+++
Range of operation	°C	-15~43	-15~24	-15~43	-15~24	-15~43	-15~24	-15~43	-15~24
Dehumidification capacity	L/h	0,6		1,4		1,8		1.8	
Air supply	m³/h	500/470/430/390/320/270/250		590/520/480/400/350/320/280		850/800/700/550/		900/800/700/600/500/400/350	
Covered surface	m²	10-16		15-22		21-31		23-34	
Noise pressure level	indoor	dB (A) 38/36/34/32/28/25/22		41/37/35/33/30/26/24		44/42/38/31/		48/45/42/37/32/30/26	
	outdoor	dB (A) 50		52		53		57	
Sound power level	indoor	dB (A) 55/48/46/44/40/37/33		56/49/47/45/42/38/36		54/52/48/41/		60/57/54/49/44/42/38	
	outdoor	dB (A) 60		63		63		65	
Indoor unit dimensions	mm	698×250×185		773×250×185		970×300×225		970x300x225	
Outdoor unit dimensions	mm	732×555×330		732×555×330		732×555×330		873x555x376	
Indoor unit weight	kg	7.5		8.5		13.5		13	
Outdoor unit weight	kg	24.5		25		26,5		36.5	
Liquid-gas line	inch	1/4" - 3/8"		1/4" - 3/8"		1/4" - 3/8"		1/4" - 1/2"	
Maximum inside-outside distance	m	15		20		25		25	
Maximum altitude difference	m	10		10		10		10	
Power supply	V-Φ-hz	220 - 1 - 50		220 - 1 - 50		220 - 1 - 50		220 - 1 - 50	
Electrical panel fuse	A	16		16		16		16	